


GENERAL INFORMATION

Composition	100% PES
Weight g/Lm	325g/m ²
Width	148cm
Min. usable Width	138cm
Roll Length	50m
Tariff code	54079200

CLEANING INSTRUCTIONS



TECHNICAL DATE

• MARTINDALE ABRASION ISO12947-2:1998	END POINT	40000		
	CHANGE IN COLOR	5		
• SEAM SLIPPAGE EN ISO 13936-2	WARP	4mm		
	WEFT	3mm		
• TEAR STRENGTH EN ISO 13937-3:2000	WARP	88N		
	WEFT	63N		
• TENSILE STRENGTH EN ISO 13934-1	WARP	1200N	elongation	31.5%
	WEFT	930N	elongation	29.5%
• COLOUR FASTNESS FOR RUBBING EN ISO 105-X12	WARP DRY	5		
	WARP WET	4/5		
	WEFT DRY	5		
	WEFT WET	4/5		
• COLOUR FASTNESS TO LIGHT	GRADE 6+	Col 17		
	GRADE 6	Col 11, 77, 87		
	GRADE 5/6	Col 50, 90		
	GRADE 5	Col 14, 34, 43,82		
	GRADE 4/5	Col 05, 08, 29, 81		
	GRADE 3/4	Col 20		
• PILLING ON MARTINDALE ISO 12945-2:2000	500 RUBS	5		
	1000 RUBS	5		
	2000 RUBS	5		
	5000 RUBS	5		
• PILLING TEST BS5811-1986	GRADE	5		
• COLOUR FASTNESS TO WATER ISO 105-E01	STAINING TO WOOL	5		
	STAINING TO ACRYL	4/5		
	STAINING TO POLYESTER	4/5		
	STAINING TO NYLON	4		
	STAINING TO COTTON	4/5		
	STAINING TO ACETATE	4		
	CHANGE IN COLOUR	4/5		